
# FilterWall™-F5 and F6

# Freestanding 3 Stage Whole House Filtration System



# 



Front view with cover

Side view with cover

Note: All dimensions are in mm.

# Specifications

Code	Temp °C	Pressure** (kPa)	Flow (Lpm)	Micron Rating*	Connection	Cartridge Size	Warranty (Years)
FILTERWALL-F5	0-52	200-875	55	5	3/4" BSP	20" x 4.5"	10^
FILTERWALL-F6	0-52	200-875	55	5	3/4" BSP	20" x 4.5"	10^

#### \*Protect from freezing.

## FILTERWALL-F5 MAINTENANCE KIT (Ordering Code: FR-F5)

Ordering Code Cartridge Size		Micron Rating (nominal)	Cartridge Description	
PL20MP2 MaxiPlus™ 4.5" x 20"		20	sediment (washable cartridge)	
PX05MP2 MaxiPlus™ 4.5" x 20"		5	polyspun sediment	
CB10MP2 MaxiPlus™ 4.5" x 20"		10	carbon block	

For a complete maintenance solution, we recommend the FR-F5 Premium Care Kit. The kit offers a full solution, including genuine replacement cartridges, O-rings, and food-grade lubricant for easy and effective maintenance.

## FILTERWALL-F6 MAINTENANCE KIT (Ordering Code: FR-F6)

Ordering Cartridge Size		Micron Rating (nominal)	Cartridge Description	
PX05MP2 MaxiPlus™ 4.5" x 20"		5	polyspun sediment	
CB10MP2	MaxiPlus™ 4.5" x 20"	10	carbon block	
SCALEPROTECT-MP2	MaxiPlus™ 4.5" x 20"	-	scale prevention	

For a complete maintenance solution, we recommend the FR-F6 Premium Care Kit. The kit offers a full solution, including genuine replacement cartridges, O-rings, and food-grade lubricant for easy and effective maintenance.

#### Warranty:

^10-year warranty is 1 year parts and labour, 9 years parts only. Excludes cartridges. Finish warranty for custom colours (Open Skies, Lime Sherbet, Sweet Apricot, Cherry Blossom, Wisteria) is 2 years. Use only genuine Puretec replacement cartridges.



Warning: Please visit www.puretec.com.au/instructions to observe essential manufacturer's instructions before use. Note: No claims can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change. This document and all lis contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systems. "Where line pressure exceeds 500KPa, an approved pressure limiting device must be installed to comply with Australian & New Zeialand Plumbing Standards. (Ref. AS 35001:2021, Clause 3.3.4). Caution: Do not use with microbiologically unsafe water or water of unknown quality without adequate disinfection before or after the system. Warranty: "Warranties in this document cover parts for the period stated and include cover for parts and labour for the first year where applicable, subject to approval. Excludes consumables. This spec sheet has been designed to help make product selection easy. However due to the complex nature of water chemistry, we strongly encourage confirming any product selection with one of our team. We may need to perform a water analysis test to confirm contaminants in water. Our Water Filtration Specialists can provide you with advice to suit your needs. "Micron rating is nominal.

## Parts Included





3-Stage Filtration System with Bypass

Property with some

User guide